

09-18-00

A

EXPRESS MAIL LABEL NO:

EL579667211US

GUNNISON, McKAY & HODGSON, L.L.P.
GARDEN WEST OFFICE PLAZA, SUITE 220
1900 GARDEN ROAD
MONTEREY, CALIFORNIA 93940
(831) 655-0880
FACSIMILE (831) 655-0888

SEPTEMBER 14, 2000

Attorney Docket No.: P-5022

Box Patent Application
Assistant Commissioner for Patents
Washington, D.C. 20231

NEW PATENT APPLICATION TRANSMITTAL LETTER
(37 C.F.R. §1.53(b))

Transmitted herewith for filing is an original(nonprovisional)
patent application of:

Inventor(s): Peter Cuong Dac Ta.

Entitled: Circuit Board Retaining Brackets

Enclosed are the following papers as required for a filing
date under 37 C.F.R. §1.53(b):

- 0 Sheets Microfiche Appendix;
- 18 Pages Description;
- 7 Pages Claims;
- 1 Page Abstract; and
- 9 Drawing Sheets(Informal).

Other papers enclosed include:

- X Return Receipt Postcard
- X Check for \$ 1270.00
- 2 Pages of Combined Declaration For Patent
Application and Power of Attorney

09/14/00
JCS20 U.S. PTO

JCS20 U.S. PTO
09/14/00
09/62225

09/14/00 09/62225

New Patent Application Transmittal Letter
Attorney Docket No. P-5022 Page 2

1 Page of Assignment of the invention to Sun
Microsystems, Inc.

X Recordation Form Cover Sheet

Fee Calculation					
Claims	Number Filed	Basic Fee Allowance	Number Extra	Rate	Basic Fee
Total No. of Claims	37	- 20 =	17	X \$18.00	\$ 306.00
No. Independent Claims	6	- 3 =	3	X \$78.00	\$ 234.00
Multiple Dependent Claims				\$260.00	0.00
				Total of above Calculation	\$1230.00
Reduction by 50% for filing by Small Entity(Enter 0.5 for small entity)					1.0
				Filing Fee	\$1230.00

FEE PAYMENT


Enclosed are:

Filing Fee	\$1230.00
Assignment Recording Fee	40.00
Total Fees Enclosed	\$1270.00

A check in the amount of \$1270.00 is enclosed

The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. 50-0553.

Respectfully submitted,


Serge J. Hodgson
Attorney for Applicant(s)
Reg. No. 40,017

004160-52235960

CIRCUIT BOARD RETAINING BRACKETS

Peter Cuong Dac Ta

5 BACKGROUND OF THE INVENTION

Field of the Invention

The present invention relates generally to retaining brackets for use in electronic devices. More particularly, the present invention relates to brackets
10 for retaining circuit boards.

Description of the Related Art

Computer systems are generally sensitive to shock and vibration. Inevitably, computer systems are
15 shipped to an end-user and, during this shipment, the computer systems are exposed to substantial shock and vibration. This shock and vibration can cause the computer system to fail.

FIG. 1 is a side plan view of a computer system 10 having a circuit board 12 attached to a mother board 14 in accordance with the prior art. As shown FIG. 1, mother board 14 included a socket 16, and circuit board 12 fit into socket 16 in a well known manner. Of importance, use of socket 16 allowed circuit board 12
20 to be readily removed from mother board 14 for replacement or repair.

To remove circuit board 12, retaining clips 18, which were pivotably attached to circuit board 12, were moved from a lock position L to an unlocked position U
30 (indicated in dashed lines). This caused retaining clips 18 to become disengaged from locking beams 20. Circuit board 12 was then slid from socket 16 and removed from mother board 14.

Disadvantageously, shock and vibration, e.g.,
35 during transportation, sometimes caused retaining clips

18 to become shook loose. Once loose, retaining clips 18 became disengage from locking beams 20 and circuit board 12 was free to move. Undesirably, circuit board 12 slid out of socket 16 as indicated by arrow 22 causing failure of computer system 10.

Even if retaining clips 18 were not shook loose, shock and vibration, e.g., during transportation, caused mother board 14 to bend and move away from circuit board 12 as indicated by arrow 24. Again, circuit board 12 undesirably slid out of socket 16 causing failure of computer system 10.

In any event, decoupling of circuit board 12 from socket 16 caused failure of computer system 10. However, to maintain customer satisfaction and to minimize service cost associated with computer system 10, is important to prevent failure of computer system 10.

SUMMARY OF THE INVENTION

In accordance with the present invention, a mother board retaining bracket is mounted to an outer circuit board housing and supports an edge of a mother board. In this manner, the mother board retaining bracket prevents the mother board from moving, e.g., during transportation, and prevents the associated failure of the computer system.

In one particular embodiment, the mother board retaining bracket includes a body having a mounting aperture, one or more upper tabs extending perpendicularly from the body, and one or more lower tabs extending perpendicularly from the body. The upper tabs lie in a first plane and the lower tabs lie in a second plane spaced apart from the first plane. The upper tabs, the lower tabs, and the body define a slot, and the edge of the mother board is supported in

slot.

5 A method of supporting the mother board includes defining a slot by the upper tabs, the body, and the lower tabs of the mother board retaining bracket. An edge of the mother board is slid into the slot. The body of the mother board retaining bracket is mounted to a circuit board housing.

10 The computer system further includes a single locker belt retaining bracket. The single locker belt retaining bracket extends across retaining clips at one end of circuit boards and thus locks the retaining clips and circuit boards in place. In this manner, the single locker belt retaining bracket prevents the retaining clips from becoming shook loose, e.g., during transportation, and prevents the associated failure of the computer system.

20 In one particular embodiment, the single locker belt retaining bracket includes an arm and a first extension attached to a first end of the arm. The first extension includes a mounting aperture. A first end of a second extension is attached to a second end of the arm. A tab is attached to a second end of the second extension.

25 To lock a retaining clip in place with the arm of the single locker belt retaining bracket, the tab is located in a slot of a first circuit board housing. A screw is passed through the mounting aperture in the first extension. The screw is threaded into a threaded structure in or adjacent a second circuit board housing. This causes the arm of the single locker belt retaining bracket to contact the retaining clip and lock it in place.

35 The computer system also includes a double locker belt retaining bracket. The double locker belt retaining bracket extends across retaining clips at

both ends of circuit boards and thus locks the retaining clips and circuit boards in place. In this manner, the double locker belt retaining bracket prevents the retaining clips from becoming shook loose, e.g., during transportation, and prevents the associated failure of the computer system.

In one particular embodiment, the double locker belt retaining bracket includes a body and a first extension attached to a first end of the body. The first extension includes a mounting aperture. A first end of a second extension is attached to a second end of the body. A second end of the second extension includes a first protrusion and a second protrusion.

To mount the double locker belt retaining bracket to a first circuit board housing and a second circuit board housing, a first mounting stud and a second mounting stud are attached to the first circuit board housing. The first protrusion of the double locker belt retaining bracket is passed around the first mounting stud.

The double locker belt retaining bracket is slid towards the first mounting stud. This allows the second protrusion to be passed around the second mounting stud. The double locker belt retaining bracket is slid towards the second mounting stud. This causes a first lip defined by the first protrusion to engage the first mounting stud and also causes a second lip defined by the second protrusion to engage the second mounting stud.

A screw is passed through the mounting aperture of the first extension. The screw is threaded into a threaded structure in or adjacent the second circuit board housing.

These and other features and advantages of the present invention will be more readily apparent from

the detailed description set forth below taken in conjunction with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

5 FIG. 1 is a side plan view of a computer system having a circuit board attached to a mother board in accordance with the prior art.

 FIG. 2 is a perspective view of a computer system having retaining brackets in accordance with one
10 embodiment of the present invention.

 FIG. 3 is a rear perspective view of a mother board retaining bracket in accordance with one embodiment of the present invention.

 FIG. 4 is a front perspective view of a mother
15 board retaining bracket in accordance with an alternative embodiment of the present invention.

 FIG. 5 is a side plan view of the mother board retaining bracket along the line V of FIG. 3 or 4 mounted to a mother board in accordance with one
20 embodiment of the present invention.

 FIG. 6 is a front plan view of the mother board retaining bracket of FIG. 3.

 FIGS. 7 and 8 are side plan views of the mother board retaining bracket of FIG. 6.

25 FIG. 9 is a perspective view of a single locker belt retaining bracket in accordance with one embodiment of the present invention.

 FIG. 10 is a side plan view of the single locker belt retaining bracket of FIG. 9 mounted across
30 retaining clips in accordance with one embodiment of the present invention.

 FIG. 11 is a perspective view of a double locker belt retaining bracket in accordance with one embodiment of the present invention.

35 FIG. 12 is a side plan view of the double locker

belt retaining bracket of FIG. 11 mounted across retaining clips in accordance with one embodiment of the present invention.

FIG. 13 is a front plan view of the double locker belt retaining bracket mounted across the retaining clips of FIG. 12.

FIG. 14 is a side plan view of the double locker belt retaining bracket of FIG. 11.

FIG. 15 is a top plan view of the double locker belt retaining bracket of FIG. 11.

In the following description, the same or similar elements are labeled with the same or similar reference numbers.

15 DETAILED DESCRIPTION

In accordance with the present invention, a mother board retaining bracket 230 (FIG. 2) is mounted to an outer circuit board housing 232 and supports an edge 214E of a mother board 214. In this manner, mother board retaining bracket 230 prevents mother board 214 from moving, e.g., during transportation, and prevents the associated failure of computer system 200.

Computer system 200 further includes a single locker belt retaining bracket 250A. Single locker belt retaining bracket 250A extends across retaining clips 218A, 218B and thus locks retaining clips 218A, 218B in place. In this manner, single locker belt retaining bracket 250A prevents retaining clips 218A, 218B from becoming shook loose, e.g., during transportation, and prevents the associated failure of computer system 200.

Computer system 200 also includes a double locker belt retaining bracket 270. Double locker belt retaining bracket 270 extends across retaining clips 218E, 218F, 218G, 218H and thus locks retaining clips 218E, 218F, 218G, 218H in place. In this manner,

double locker belt retaining bracket 270 prevents retaining clips 218E, 218F, 218G, 218H from becoming shook loose, e.g., during transportation, and prevents the associated failure of computer system 200.

5 More particularly, FIG. 2 is a perspective view of a computer system 200 having retaining brackets 230, 250A, 250B, and 270 in accordance with one embodiment of the present invention. Computer system 200 includes a mother board 214. Mother board 214 includes a first
10 socket 216A in a conventional manner. A circuit board 212A, perpendicular to mother board 214, is mounted in socket 216A as those of skill in the art will understand.

In accordance with this embodiment, an outer
15 circuit board housing 232 is adjacent circuit board 212A. Outer circuit board housing 232 is parallel to circuit board 212A and perpendicular to mother board 214. Retaining bracket 230, hereinafter referred to as a mother board retaining bracket 230, is mounted to
20 outer circuit board housing 232 and supports an edge 214E of mother board 214. As discussed below in greater detail with reference to FIGS. 3, 4, and 5, mother board retaining bracket 230 supports mother board 214 and prevents undesirable movement of mother
25 board 214 away from circuit board 212A and prevents the associated failure of computer system 200.

Computer system 200 further includes a second circuit board 212B and a third circuit board 212C. Circuit board 212B includes a retaining clip 218A and
30 circuit board 212C includes a retaining clip 218B. Circuit boards 212B, 212C are mounted in sockets on a mother board (not shown in the view of FIG. 2, see FIG. 10). Retaining clips 218A, 218B are engaged with a locking beam 220A thus holding circuit boards 212B,
35 212C in place.

5 Circuit boards 212B, 212C are contained within an enclosure defined by an outer circuit board housing 252 and an inner circuit board housing 254. To prevent retaining clips 218A, 218B from becoming shook loose, e.g., during transportation, retaining bracket 250A, hereinafter referred to as a single locker belt retaining bracket 250A, is mounted to circuit board housings 252, 254. Single locker belt retaining bracket 250A extends from outer circuit board housing 10 252 across retaining clips 218A, 218B and to inner circuit board housing 254. As discussed in greater detail below with reference to FIGS. 9 and 10, single locker belt retaining bracket 250A locks retaining clips 218A, 218B in place and prevents retaining clips 15 218A, 218B from becoming shook loose, e.g., during transportation.

20 Circuit board 212B further includes a retaining clip 218C and circuit board 212C further includes a retaining clip 218D. Retaining clips 218C, 218D are engaged with a locking beam 220B thus holding circuit boards 212B, 212C in place. In a manner similar to that described above with respect to single locker belt retaining bracket 250A, retaining bracket 250B, hereinafter referred to as a single locker belt 25 retaining bracket 250B, extends from outer circuit board housing 252 across retaining clips 218C, 218D and to inner circuit board housing 254. By extending across retaining clips 218C, 218D, single locker belt retaining bracket 250B locks retaining clips 218C, 218D 30 in place and prevents retaining clips 218C, 218D from becoming shook loose, e.g., during transportation.

35 Computer system 200 further includes a circuit board 212D adjacent circuit board 212A. Circuit board 212D is mounted in a socket 216B of mother board 214 in a manner similar to that discussed above in regards to

circuit board 212A and socket 216A.

Circuit board 212A includes retaining clips 218E, 218F and circuit board 212D includes retaining clips 218G, 218H. Retaining clips 218E, 218G and retaining
5 clips 218F, 218H are engaged with locking beams 220C, 220D, respectively, thus holding circuit boards 212A, 212D in place.

Circuit boards 212A, 212D are contained within an enclosure defined by outer circuit board housing 232
10 and an inner circuit board housing 234. To prevent retaining clips 218E, 218F, 218G, 218H from becoming shook loose, e.g., during transportation, a retaining bracket 270, hereinafter referred to as a double locker
belt retaining bracket 270, is mounted to circuit board
15 housings 232, 234. Double locker belt retaining bracket 270 extends from outer circuit board housing 232 across retaining clips 218E, 218F, 218G, 218H and to inner circuit board housing 234. As discussed in
greater detail below with reference to FIGS. 11, 12 and
20 13, double locker belt retaining bracket 270 locks retaining clips 218E, 218F, 218G, 218H in place and prevents retaining clips 218E, 218F, 218G, 218H from becoming shook loose, e.g., during transportation.

FIG. 3 is a rear perspective view of a mother
25 board retaining bracket 230A in accordance with one embodiment of the present invention. Mother board retaining bracket 230A includes a body 302, which is planar. Body 302 includes a first mounting aperture 304A and a second mounting aperture 304B, collectively
30 referred to as mounting apertures 304.

Mother board retaining bracket 230A includes at least one upper, e.g., first, tab 310 and, more particularly, includes upper tabs 310A and 310B, collectively referred to as upper tabs 310. Mother
35 board retaining bracket 230A further includes at least

one lower, e.g., second, tab 312. Upper tabs 310 and lower tab 312 are formed along a lower, e.g., first, edge 302E of body 302. In this embodiment, upper tabs 310 and lower tab 312 extend perpendicularly from body 302.

FIG. 4 is a front perspective view of a mother board retaining bracket 230B in accordance with an alternative embodiment of the present invention. Mother board retaining bracket 230B of FIG. 4 is similar to mother board retaining bracket 230A of FIG. 3 and only the significant differences are discussed below.

Referring now to FIG. 4, mother board retaining bracket 230B includes a plurality of upper tabs 310 interleaved with a plurality of lower tabs 312. More particularly, between each adjacent upper tab 310 is a lower tab 312 and vice versa. To illustrate, the plurality of upper tabs 310 include upper tabs 310A, 310B and the plurality of lower tabs 312 include lower tabs 312A, 312B. Lower tab 312A is between upper tab 310A and upper tab 310B in the longwise, e.g., first, direction in the view of FIG. 4. Similarly, upper tab 310B is between lower tab 312A and lower tab 312B.

FIG. 5 is a side plan view of mother board retaining bracket 230A or 230B along the line V of FIG. 3 or 4, respectively, mounted to a mother board 214A in accordance with one embodiment of the present invention.

As shown in FIG. 5, upper tab(s) 310, body 302 and lower tab(s) 312 define a slot 502. Generally, upper tab(s) 310 lie in a first plane P1 and lower tab(s) 312 lie in a second plane P2, spaced apart and parallel to plane P1. The width of slot 502, e.g., see characteristic A8 of FIG. 8 for example, is equal to or slightly greater than the width WMB of mother board

214A. Accordingly, edge 214E of mother board 214A, e.g., a printed circuit board, fits tightly into slot 502 such that an upper, e.g., first surface 214U of mother board 214A is supported by upper tab(s) 310 and a lower, e.g., second, surface 214L of mother board 214A is supported by lower tab(s) 312.

Body 302 of mother board retaining bracket 230A (or 230B) is mounted to an outer circuit board housing 232A by screws 504. More particularly, edge 214E of mother board 214A is slid into slot 502 and screws 504 are passed through mounting apertures 304 and are threaded into outer circuit board housing 232A and/or a bolt or other threaded structure in or adjacent outer circuit board housing 232A. In the above manner, edge 214E of mother board 214A is supported in slot 502 thus preventing mother board 214A from moving, e.g., during transportation.

FIG. 6 is a front plan view of mother board retaining bracket 230A of FIG. 3 in accordance with one embodiment to the present invention. In one embodiment, mother board retaining bracket 230A is hard steel, which has been stamped and bent as those of skill in the art will understand. Illustrative specifications for the various characteristics illustrated FIG. 6 are set forth below in Table 1.

TABLE 1

CHARACTERISTIC	SPECIFICATION
A6	R2.25 mm
B6	28.00 mm
C6	R1.50 mm
D6	75.88 mm
E6	49.12 mm
F6	12.00 mm
G6	34.12 mm
H6	35.00 mm

I6	7.80 mm
J6	9.12 mm
K6	111.76 mm
L6	140.00 mm

FIG. 7 is a side plan view of mother board retaining bracket 230A of FIG. 6. An illustrative specification for the various characteristics illustrated FIG. 7 is set forth below in Table 2.

TABLE 2

CHARACTERISTIC	SPECIFICATION
A7	40.00 mm

FIG. 8 is another side plan view of mother board retaining bracket 230A of FIG. 6. Illustrative specifications for the various characteristics illustrated FIG. 8 are set forth below in Table 3.

TABLE 3

CHARACTERISTIC	SPECIFICATION
A8	3.00 mm
B8	2.00 mm
C8	1.20 mm

FIG. 9 is a perspective view of a single locker belt retaining bracket 250 in accordance with one embodiment of the present invention. Single locker belt retaining bracket 250 includes an arm 902, a first extension 904 attached to a first end 902E1 of arm 902 and a second extension 906 attached to a second end 902E2 of arm 902 opposite first end 902E1. In this embodiment, extensions 904, 906 extend perpendicularly from arm 902. Illustratively, the distance between extension 904 and extension 906 is 106.00 mm. In one embodiment, single locker belt retaining bracket 250 is hard steel, which has been stamped and bent as those of skill in the art will understand.

Extension 904 includes a mounting aperture 908, illustratively, having a specification of R2.50 mm. A

first end 906E1 of extension 906 is attached to arm 902. A tab 910 extends perpendicularly from, and is attached to, a second end 906E2 of extension 906 opposite end 906E1. Tab 910 is parallel to arm 902.

5 As discussed below in greater detail with reference to FIG. 10, mounting aperture 908 and tab 910 facilitate mounting of single locker belt retaining bracket 250 to the circuit board housings.

10 Rails 912A, 912B are along the length of arm 902 and extend perpendicularly from arm 902. Rails 912A, 912B provide strength and rigidity of arm 902.

FIG. 10 is a side plan view of single locker belt retaining bracket 250 of FIG. 9 mounted across retaining clips 218A, 218B in accordance with one
15 embodiment of the present invention. As shown in FIG. 10, circuit boards 212B, 212C are mounted in sockets 216C, 216D, respectively, of a mother board 214B. Circuit boards 212B, 212C include retaining clips 218A, 218B, respectively.

20 Single locker belt retaining bracket 250 is mounted to an inner circuit board housing 254A and an outer circuit board housing 252A. More particularly, extension 904 is mounted to outer circuit board housing 252A by a screw 1002 passing through mounting aperture
25 908 of extension 904 and being threaded into outer circuit board housing 252A and/or a bolt or other threaded structure in or adjacent outer circuit board housing 252A. Further, extension 906 is mounted to inner circuit board housing 254A by tab 910, which is
30 located in a slot 1004 in inner circuit board housing 254A.

Advantageously, arm 902 contacts and locks in place retaining clips 218A, 218B. In this manner, single locker belt retaining bracket 250 prevents
35 retaining clips 218A, 218B from becoming shook loose,

e.g., during transportation, and prevents the associated failure of computer system 200.

In one embodiment, arm 902 includes a compliant pad on a lower, e.g., first, surface 902L of arm 902 and this compliant pad contacts retaining clips 218A, 218B. An example of a suitable compliant pad is an adhesive back silicon pad such as a 10mm x 90mm x 2.5mm thick medium silicon pad available from Boyd Corporation, 600 South McClure Road, Modesto, CA 95357, (209) 236-1111 as part number R10460.

Of importance, tab 910 in combination with slot 1004 allow single locker belt retaining bracket 250 to be easily installed and removed. Typically, inner circuit board housing 254A is directly adjacent a second inner circuit board housing 234A and the space between inner circuit board housings 254A and 234A is relatively small. However, to mount single locker belt retaining bracket 250 to inner circuit board housing 254A, tab 910 is simply moved and snapped or otherwise placed into slot 1004. Advantageously, mechanical manipulation of a screw or other mounting structure within the small space between inner circuit board housings 254A and 234A is avoided.

After tab 910 is placed in slot 1004, screw 1002 is passed through mounting aperture 908 and is threaded into outer circuit board housing 252A and/or a bolt or other threaded structure in or adjacent outer circuit board housing 252A. Of importance, ample space for manipulation of screw 1002 is typically available.

FIG. 11 is a perspective view of a double locker belt retaining bracket 270A in accordance with one embodiment of the present invention. Double locker belt retaining bracket 270A includes a body 1102, a first extension 1108 attached to a first end 1102E1 of body 1102 and a second extension 1110 attached to a

second end 1102E2 of body 1102 opposite first end 1102E1. In this embodiment, extensions 1108, 1110 extend perpendicularly from body 1102. Extension 1108 includes a first mounting aperture 1114A and a second mounting aperture 1114B, collectively referred to as mounting apertures 1114. In one embodiment, double locker belt retaining bracket 270A is hard steel, which has been stamped and bent as those of skill in the art will understand.

10 Body 1102 includes a first arm 1104A, a second arm 1104B and a support beam 1106 integrally attached together at ends 1102E1, 1102E2 of body 1102. Rails 1112 are along the lengths of arms 1104A, 1104B and extend perpendicularly from arms 1104A, 1104B. More
15 particularly, each of arms 1104A, 1104B includes two of rails 1112. Rails 1112 provide strength and rigidity to arms 1104.

 A first end 1110E1 of extension 1110 is attached to body 1102. Of importance, a second end 1110E2 of
20 extension 1110 is flared to have a greater length LE2 than a length LE1 of first end 1110E1. Stated another way, extension 1110 includes protrusions 1116A, 1116B, opposite one another, at second end 1110E2. Protrusions 1116A, 1116B define lips 1118A, 1118B,
25 respectively. Protrusions 1116A, 1116B and lips 1118A, 1118B collectively are referred to as protrusions 1116 and lips 1118, respectively. In this embodiment, lips 1118 are parallel to body 1102. A rail 1120 is along the length of second end 1110E2 and extends
30 perpendicularly from extension 1110. Rail 1120 provides strength and rigidity of extension 1110.

 FIG. 12 is a side plan view of double locker belt retaining bracket 270A of FIG. 11 mounted across retaining clips 218E, 218F, 218G, 218H in accordance
35 with one embodiment of the present invention. FIG. 13

is a front plan view of double locker belt retaining bracket 270A mounted across retaining clips 218E, 218F, 218G, 218H of FIG. 12.

Referring now to FIGS. 12 and 13 together, double
5 locker belt retaining bracket 270A is mounted to an inner circuit board housing 234B and an outer circuit board housing 232B. More particularly, extension 1108 is mounted to outer circuit board housing 232B by screws 1302 passing through mounting apertures 1114 of
10 extension 1108, which are threaded into outer circuit board housing 232B and/or a bolt or other threaded structure in or adjacent outer circuit board housing 232B. Further, extension 1110 is mounted to inner circuit board housing 234B by protrusions 1116A, 1116B,
15 which are positioned below mounting studs 1202A, 1202B, respectively, extending from inner circuit board housing 234B.

Advantageously, arm 1104A contacts and locks in place retaining clips 218E, 218G of circuit boards
20 212A, 212D, respectively. Similarly, arm 1104B contacts and locks in place retaining clips 218F, 218H of circuit boards 212A, 212D, respectively. In this manner, double locker belt retaining bracket 270A prevents retaining clips 218E, 218F, 218G, 218H from
25 becoming shook loose, e.g., during transportation, and prevents the associated failure of computer system 200.

Of importance, protrusions 1116A, 1116B in combination with mounting studs 1202A, 1202B allow double locker belt retaining bracket 270A to be easily
30 installed and removed. Typically, inner circuit board housing 234B is directly adjacent a second inner circuit board housing 254B and the space between inner circuit board housings 234B and 254B is relatively small.

35 To allow double locker belt retaining bracket 270A

to be easily installed and removed, mounting studs 1202A, 1202B are attached to inner circuit board housing 234B. Illustratively, mounting studs 1202A, 1202B are pegs, washers and/or screw heads mounted to inner circuit board housing 234B.

Referring now to FIG. 12, to mount double locker belt retaining bracket 270A to inner circuit board housing 234B, protrusion 1116A (or 1116B) is passed around and below mounting stud 1202A (or 1202B).

Double locker belt retaining bracket 270A is slid horizontally left towards mounting stud 1202A (or right towards mounting stud 1202B) in the view of FIG. 12 until extension 1110 is wedged against mounting stud 1202A (or 1202B) preventing any further motion of double locker belt retaining bracket 270A.

Protrusion 1116B (or 1116A) is then passed down around mounting stud 1202B (or 1202A). Double locker belt retaining bracket 270A is slid horizontally right towards mounting stud 1202B (or left towards mounting stud 1202A) such that lips 1118A, 1118B engage mounting studs 1202A, 1202B, respectively. Referring again to FIGS. 12 and 13 together, mechanical manipulation of a screw or other mounting structure within the small space between inner circuit board housings 234B and 254B is avoided.

After lips 1118A, 1118B are engaged with mounting studs 1202A, 1202B, respectively, screws 1302 (FIG. 13) are passed through mounting apertures 1114 and are threaded into outer circuit board housing 232B and/or a bolt or other threaded structure in or adjacent outer circuit board housing 232B. Of importance, ample space for manipulation of screws 1302 is typically available.

FIG. 14 is a side plan view of double locker belt retaining bracket 270A of FIG. 11. Illustrative specifications for the various characteristics

illustrated in FIG. 14 are set forth below in Table 4.

TABLE 4

CHARACTERISTIC	SPECIFICATION
A14	R2.50 mm
B14	31.30 mm

FIG. 15 is a top plan view of double locker belt retaining bracket 270A of FIG. 11. Illustrative
5 specifications for the various characteristics illustrated in FIG. 15 are set forth below in Table 5.

TABLE 5

CHARACTERISTIC	SPECIFICATION
A15	85.40 mm
B15	Apply Boyd adhesive backed medium silicon (Boyd part number R10460), size 10mm x 90mm x 2.4 mm thick, to underside surface.

The drawings and the forgoing description gave examples of the present invention. The scope of the
10 present invention, however, is by no means limited by these specific examples. Numerous variations, whether explicitly given in the specification or not, such as differences in structure, dimension, and use of material, are possible. For example, although the
15 terms parallel and perpendicular are used in relation to various structures, it is understood that the various structures may not be exactly parallel or perpendicular but only substantially parallel or perpendicular. The scope of the invention is at least
20 as broad as given by the following claims.

CLAIMS

I CLAIM:

1. A structure comprising a retaining bracket,
said retaining bracket comprising:

5 a body having a mounting aperture;

one or more upper tabs extending perpendicularly
from said body, said one or more upper tabs lying in a
first plane; and

10 one or more lower tabs extending perpendicularly
from said body, said one or more lower tabs lying in a
second plane spaced apart from said first plane.

2. The structure of Claim 1 wherein said second
plane is parallel to said first plane.

15

3. The structure of Claim 1 wherein said one or
more upper tabs comprises a first upper tab and a
second upper tab.

20

4. The structure of Claim 3 wherein said one or
more lower tabs comprises a first lower tab between
said first upper tab and said second upper tab.

25

5. The structure of Claim 4 wherein said one or
more lower tabs further comprises a second lower tab,
said first upper tab being between said first lower tab
and said second lower tab.

30

6. The structure of Claim 1 wherein said one or
more lower tabs, said one or more upper tabs, and said
body define a slot.

35

7. The structure of Claim 6 further comprising a
printed circuit board having an edge supported in said
slot.

8. The structure of Claim 7 wherein a first surface of said printed circuit board is supported by said one or more upper tabs and a second surface of said printed circuit board is supported by said one or more lower tabs.

9. The structure of Claim 7 wherein said printed circuit board is a mother board.

10. A method of supporting a printed circuit board comprising:
defining a slot by one or more upper tabs lying in a first plane, a body, and one or more lower tabs lying in a second plane spaced apart from said first plane;
sliding an edge of said printed circuit board into said slot; and
mounting said body to a circuit board housing.

11. The method of Claim 10 wherein said mounting said body to a circuit board housing comprises:
passing a screw through a mounting aperture of said body; and
threading said screw into a threaded structure in or adjacent said circuit board housing.

12. The method of Claim 10 wherein a first surface of said printed circuit board is supported by said one or more upper tabs and a second surface of said printed circuit board is supported by said one or more lower tabs.

13. The method of Claim 10 wherein said printed circuit board is a mother board.

14. A structure comprising a retaining bracket,
said retaining bracket comprising:

an arm;

5 a first extension attached to a first end of said
arm, said first extension comprising a mounting
aperture;

a second extension having a first end attached to
a second end of said arm; and

10 a tab attached to a second end of said second
extension.

15 15. The structure of Claim 14 wherein said first
extension is perpendicular to said arm and said second
extension is perpendicular to said arm.

16. The structure of Claim 15 wherein said tab is
perpendicular to said second extension and parallel to
said arm.

20 17. The structure of Claim 14 further comprising
a rail along a length of said arm and extending
perpendicularly from said arm.

25 18. The structure of Claim 17 wherein said rail
provides strength and rigidity of said arm.

19. The structure of Claim 14 further comprising
a circuit board having a retaining clip, said arm
contacting and locking in place said retaining clip.

30 20. The structure of Claim 19 further comprising:
a first circuit board housing; and
a second circuit board housing, said retaining
bracket being mounted to said first circuit board
35 housing and said second circuit board housing.

21. The structure of Claim 20 wherein said first circuit board housing comprises a slot, said second extension being mounted to said first circuit board housing by locating said tab in said slot.

22. The structure of Claim 21 further comprising a screw, said first extension being mounted to said second circuit board housing by said screw, said screw passing through said mounting aperture and being threading into a threaded structure in or adjacent said second circuit board housing.

23. A method of locking a retaining clip in place with an arm of a retaining bracket comprising:
locating a tab of said retaining bracket in a slot of a first circuit board housing;
passing a screw through a mounting aperture in a first extension of said retaining bracket extending from said arm; and
threading said screw into a threaded structure in or adjacent a second circuit board housing, wherein said arm contacts said retaining clip.

24. The method of Claim 23 wherein said tab is attached to said arm by a second extension of said retaining bracket.

25. The method of Claim 23 wherein a circuit board comprising said retaining clip is contained within an enclosure defined by said first circuit board housing and said second circuit board housing.

26. A structure comprising a retaining bracket, said retaining bracket comprising:

a body;

a first extension attached to a first end of said body, said first extension comprising a mounting aperture; and

- 5 a second extension, a first end of said second extension attached to a second end of said body, a second end of said second extension including a first protrusion and a second protrusion.

- 10 27. The structure of Claim 26 wherein said body comprises:

a first arm;

a second arm; and

- 15 a support beam, said first arm, said second arm, and said support beam being integrally attached together at said first end and said second end of said body.

- 20 28. The structure of Claim 27 further comprising a plurality of rails along lengths of said first arm and said second arm, said rails providing strength and rigidity to said first arm and said second arm.

- 25 29. The structure of Claim 26 wherein said first extension and said second extension are perpendicular to said body.

- 30 30. The structure of Claim 29 further comprising:
a first lip defined by said first protrusion;
a second lip defined by said second protrusion.

31. The structure of Claim 30 wherein said first lip and said second lip are parallel to said body.

- 35 32. The structure of Claim 30 further comprising:

a first circuit board housing;
a first mounting stud extending from said first
circuit board housing, said first mounting stud engaged
with said first lip; and

- 5 a second mounting stud extending from said first
circuit board housing, said second mounting stud
engaged with said second lip.

33. The structure of Claim 32 further comprising:
10 a second circuit board housing;
a screw passing through said mounting aperture and
threaded into a threaded structure in or adjacent said
second circuit board housing.

- 15 34. The structure of Claim 33 wherein said first
extension is mounted to said second circuit board
housing and wherein said second extension is mounted to
said first circuit board housing.

- 20 35. A method of mounting a retaining bracket to a
first circuit board housing and a second circuit board
housing comprising:

- attaching a first mounting stud and a second
mounting stud to said first circuit board housing;
25 passing a first protrusion of said retaining
bracket around said first mounting stud;
sliding said retaining bracket towards said first
mounting stud;
passing a second protrusion of said retaining
30 bracket around said second mounting stud; and
sliding said retaining bracket towards said second
mounting stud.

36. The method of Claim 35 wherein said sliding
35 said retaining bracket towards said second mounting

stud causes a first lip defined by said first protrusion to engage said first mounting stud and causes a second lip defined by said second protrusion to engage said second mounting stud.

5

37. The method of Claim 35 further comprising:
passing a screw through a mounting aperture of
said retaining bracket; and

threading said screw into a threaded structure in
10 or adjacent said second circuit board housing.

CIRCUIT BOARD RETAINING BRACKETS

Peter Cuong Dac Ta

ABSTRACT

5 A mother board retaining bracket is mounted to an
outer circuit board housing and supports an edge of a
mother board. The mother board retaining bracket
prevents the mother board from moving, e.g., during
transportation, and prevents the associated failure of
the computer system. The computer system further
10 includes single and double locker belt retaining
brackets. The single locker belt retaining bracket
extends across a retaining clip on one side of a
circuit board and locks the retaining clip in place.
The double locker belt retaining bracket extends across
15 retaining clips on both sides of a circuit board and
locks the retaining clips in place. In this manner,
the single and double locker belt retaining brackets
prevent the retaining clips from becoming shook loose.




FIG. 1

PRIOR ART

700 ↗







FIG. 2



004160-52229960






FIG. 9





FIG. 10







FIG. 15

COMBINED DECLARATION FOR PATENT APPLICATION
AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below adjacent to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of subject matter (process, machine, manufacture, or composition of matter, or an improvement thereof) which is claimed and for which a patent is sought by way of the application entitled "Circuit Board Retaining Brackets" which

☒ is attached hereto.

☐ and is amended by the Preliminary Amendment attached hereto.

☐ was filed on _____

as Application Serial No. _____

☐ and was amended on _____ (if applicable).

I hereby state that I have reviewed and understand the contents of the specification, including the claims of the application entitled "Circuit Board Retaining Brackets", as amended by any amendment referred to above.

I acknowledge the duty to disclose information known to me which is material to patentability of this application in accordance with Title 37, Code of Federal Regulations, § 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or 365(b) of any foreign application(s) for patent or inventor's certificate, or 365(a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below any foreign application for patent or inventor's certificate, or of any PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application(s)			Priority Claimed
NA			<input type="checkbox"/> Yes <input type="checkbox"/> No
(Number)	(Country)	(Day/Month/Year Filed)	
NA			<input type="checkbox"/> Yes <input type="checkbox"/> No
(Number)	(Country)	(Day/Month/Year Filed)	
NA			<input type="checkbox"/> Yes <input type="checkbox"/> No
(Number)	(Country)	(Day/Month/Year Filed)	

I hereby claim the benefit under Title 35, United States Code §120 of any United States application(s), or 365(c) of any PCT international application designating the United States of America, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of Title 35, United States Code, §112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

<u>NA</u>		
(Application Serial No.)	(Filing Date)	(Status-patented, pending, abandoned)
<u>NA</u>		
(Application Serial No.)	(Filing Date)	(Status-patented, pending, abandoned)
<u>NA</u>		
(Application Serial No.)	(Filing Date)	(Status-patented, pending, abandoned)

I hereby appoint the attorney(s) and/or agent(s) assigned to the Customer Number below to prosecute this application and to transact all business in the United States Patent and Trademark Office connected therewith:

Customer Number 24209

Address all correspondence and telephone calls to:

Serge J. Hodgson
Gunnison, McKay & Hodgson, L.L.P.
Garden West Office Plaza, Suite 220
1900 Garden Road
Monterey, CA 93940

Telephone: 831-655-0880
Facsimile: 831-655-0888

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Title 18, United States Code, § 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole or first inventor Peter Cuong Dac Ta
 Inventor's signature Peter Cu Date 9/9/82
 Residence Hayward, CA Citizenship U.S.
 Post Office Address 1973 Gerald Way
Hayward, CA 94545